

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 84
Hercules Heavy Duty Furnace/Stove
Cement



MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc.
111 South Street
Passaic NJ 07055
Phone (800) 221-9330
Fax (800) 333-3456

Date Prepared: 9/2/1993 Last Reviewed: 9/2/1993

Meets OSHA 29 CFR 1910.1200

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s), CAS Numbers)	OSHA PEL	ACGIH TLV	Other Limits	Upper Bound Limit if SARA Reportable
*Totally encapsulated in wet paste. Does not present any respirable dust hazard.				
Sodium Silicate (1344-09-8)	N/E	N/E	N/A	--
*Silicon Dioxide (14808-60-7)	N/A	N/A	N/A	--

HMIS Hazard Rating: Health: 2 Flammability: 0 Reactivity: 0 Personal Protection A

Section 3 - Physical/Chemical Characteristics

Boiling Point (°C):	Specific Gravity (H ₂ O = 1):	Vapor Density (Air = 1):	Vapor Pressure (mm Hg):
N/A	1.75	N/A	N/A
Melting Point (° F)	Evaporation Rate: (Butyl Acetate = 1)	Solubility in Water:	
N/A	N/A	Slightly soluble in water and water miscible	
Appearance And Color:	Dark Gray/Black colored paste	Odor:	No Odor

Section 4 - Fire And Explosion Hazard Data

Flash Point:	Flammable Limits:	LEL:	UEL:
N/A	N/A	N/A	N/A

Extinguishing Media: Non-flammable. Use appropriate for surrounding fire.

Special Firefighting Procedures:
None

Unusual Fire And Explosion Hazards:
None

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable Conditions To Avoid: None

Incompatibility Product is alkaline. Avoid contact with acidic materials.
(Materials To Avoid):

Hazardous Decomposition: None

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry: Inhalation N/A Skin Yes/Primary Ingestion Yes/Secondary

Health Hazards:

Prolonged contact with skin can cause irritation. Contact with eyes or open abraded skin can cause severe irritation with superficial destruction of skin tissue.

Carcinogenicity: NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

Will cause skin irritation on continued contact.

Medical Conditions Generally Aggravated By Exposure:

None known.

Emergency And First Aid Procedures:

INGESTION: Do not induce vomiting. Dilute with water or milk. Get medical attention. SKIN: Wash with plenty of water for at least 15 minutes. EYES: Flush the material out immediately with plenty of water. Get medical attention.

Continued on Next Page

DISCONTINUED

Section 7 - Precautions For Safe Handling And Use:**Steps To Be Taken In Case Material Is Released Or Spilled:**

This material is in the form of a paste. Use absorbent material and sweep up.

Waste Disposal Method:

Non-hazardous landfill.

Precautions To Be Taken In Handling And Storing:

None

Other Precautions:

None

Section 8 - Control Measures:**Respiratory Protection:**

None required.

Ventilation: Local Exhaust Adequate
Mechanical N/A

Special N/A

Gloves: Rubber gloves.

Other: N/A

Eye Protection: Goggles

Other Protective Clothing: Standard work clothing.

Work/Hygienic Practices Wash thoroughly after handling.



FACTS
axed
AST!

For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.