

electrical contact cleaner

Spec Sheet #S00103
July 2003

Contact Cleaner (Non-Conductive)



specifications

electrical
contact
cleaner

DESCRIPTION

Hercules electrical contact cleaner is a unique combination of solvents and propellants for removing oil, dirt and moisture from the surface of contact points on small electrical equipment, controls, ignition systems, motors, relays and thermostats. The solvent flushes off oil, grease and metallic oxides caused by corrosion or arcing, while leaving a clean, dry, residue-free surface. This non-conductive **electrical contact cleaner** lifts dirt and dust particles from contact surfaces.

Contains no CFC's or chlorinated ingredients.

SIZES AND PACKING

STOCK NO.	SIZE	PACKING	WEIGHT/CASE
35180	11 oz.	12	12.6 lbs.

electrical contact cleaner

Contact Cleaner (Non-Conductive)

APPROVALS AND LISTINGS

Not applicable.

SPECIFIC USES

Hercules electrical contact cleaner is used to remove grease dirt and dust particles from contact surfaces.

SPECIFIC APPLICATIONS*

Apply on contacts in electronic equipment, motor controls, ignition systems, relays and thermostats.

PHYSICAL PROPERTIES

Specific Gravity	.77
Solubility in water:	Negligible
Boiling Point (°F):	191°F
Vapor Pressure:	95 psig @ 70°F
Appearance and color:	Clear colorless liquid with faint petroleum odor.

WARNINGS OR CAUTIONS

- **EXTREMELY FLAMMABLE.** Do not store near fire, heated surfaces, sparks, or flames.
- Read all cautions and directions carefully before using this product.
- Be certain electric equipment is turned off before cleaning and wait until surface is thoroughly dry before returning power to system.
- Avoid contact with eyes and skin.
- Use in well ventilated areas. Intentional misuse of aerosol products by inhaling concentrated vapors may be harmful or fatal.
- Dispose of can in accordance with Federal, State and local regulations.
- Contents under pressure. Do not store at temperatures over 120°F.
- Do not puncture or incinerate container.
- **DO NOT USE ON PLASTIC.**

DIRECTIONS FOR USE

SHAKE WELL BEFORE USING. If using on electric equipment or machinery, turn off equipment and wait until surface is thoroughly dry before returning power. Hold can upright 6 or 8 inches from surface. After spraying area to be cleaned allow to dry then wipe or brush clean. Test in small inconspicuous area before applying. Do not use on plastic.



MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #103

For Delivery by Fax	Call 1-800-942-4636
Internet	See MSDS section of www.herchem.com
Mail	Contact Hercules at address below or any Hercules representative

HMIS Hazard warning 1-4-0-G.

INGREDIENTS CAS#

Petroleum Distillates	64742-48-9
Carbon Dioxide	124-38-9

* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100
 Phone: 800-221-9330 • Fax: 800-333-3456
 e-mail: info@herchem.com
<http://www.herchem.com>

