

fast dry degreaser

Degreaser



DESCRIPTION

Hercules fast dry degreaser removes grease and oil quickly from most surfaces without rinsing. Ideal for degreasing oil burners, mechanical parts, HVAC equipment, and refrigeration coils. Specially formulated to air dry and leave no film or residue. Safe on most plastic, cement and metal surfaces.

Contains no CFC's, no petroleum distillates and is non-chlorinated.

SIZES AND PACKING

STOCK NO.	SIZE	PACKING	WEIGHT/CASE
35182	16 oz.	12	15.6 lbs.



specifications

fast dry
degreaser

fast dry degreaser

Degreaser

APPROVALS AND LISTINGS

Not applicable.

SPECIFIC USES

Hercules fast dry degreaser is used to remove grease, grime, soot and most other oils and dirt from metal or hard surfaces.

SPECIFIC APPLICATIONS*

Apply on most machinery and equipment, any metal or hard surfaces including refrigeration coils, HVAC equipment, and other machine parts.

PHYSICAL PROPERTIES


Specific Gravity	.73
Solubility in water:	< 10%
Boiling Point (°F):	94°F
Vapor Pressure:	40 psig @ 70°F
Appearance and color:	Clear colorless liquid with mild orange odor.

WARNINGS OR CAUTIONS

- **EXTREMELY FLAMMABLE.** Do not store near fire, heated surfaces, sparks, or flames.
- Read all cautions and directions carefully before using this product.
- Avoid contact with eyes and skin.
- Use in well ventilated areas. Intentional misuse of aerosol products by inhaling concentrated vapors may be harmful or fatal.
- Dispose of can in accordance with Federal, State and local regulations.
- Contents under pressure. Do not store at temperatures over 120°F.
- Do not puncture or incinerate can.
- May affect painted surfaces. Test in small area before applying.

DIRECTIONS FOR USE

SHAKE WELL BEFORE USING. Protect walls and floors from dripping. Hold can upright while thoroughly saturating area with spray. Wipe residue away. No rinsing required.



MATERIAL SAFETY INFORMATION

FOR MORE INFORMATION ON THIS PRODUCT, REQUEST MATERIAL SAFETY DATA SHEET (MSDS) #102

For Delivery by Fax	Call 1-800-942-4636
Internet	See MSDS section of www.herchem.com
Mail	Contact Hercules at address below or any Hercules representative

HMIS Hazard warning 1-4-0-G.

INGREDIENTS CAS#

Acetone	67-64-1
Heptane	142-82-5
D-Limonene	5989-27-5
Carbon Dioxide	124-38-9

* For special applications which may not be covered on this or other Hercules literature, please contact Hercules Technical Services Department by phone at 1-800-221-9330 or send a fax to 1-800-333-3456.



Hercules Chemical Company, Inc.

111 South Street, Passaic, NJ 07055-9100
 Phone: 800-221-9330 • Fax: 800-333-3456
 e-mail: info@herchem.com
<http://www.herchem.com>

